The Naiad Frigate Addendum 2 – Printing Patterns

Make sure to print all patterns at Actual Size. PDF readers often open the print dialog box with settings used the previous printing. The images below show the correct printer settings for Adobe Reader and Adobe Acrobat.

You can check a printed pattern. Print one of the dead flat patterns and measure the maximum moulded breadth. This dimension should be 38' 9". At 1:60 this is 7.75" actual measure. This will confirm that the correct setting is being used. If correct, use that setting for all pattern printing.

Adobe Reader

Set the Page Scaling Option to "None" as shown below.

Print	×
Printer Name: EPSON Stylus Photo 1400 Series Status: Ready Type: EPSON Stylus Photo 1400 Series	Properties Comments and Forms: Document and Markups
Print Range Image Image <th>Preview: Composite k 8.5 10 11 11 11 10 11 10 10 10 10</th>	Preview: Composite k 8.5 10 11 11 11 10 11 10 10 10 10
Printing Tips Advanced	OK Cancel

Adobe Acrobat

Set the Size Option to "Actual Size as shown below.

Print	×
Printer: EPSON Stylus Photo 1400 Series Properties Advanced	Help 🕢
Pages to Print All Current page Pages 1 More Options Page Sizing & Handling (a) Size Options: Size Options: Fit Actual size Shrink oversized pages Choose paper source by PDF page size Print on both sides of paper Orientation: Auto portrait/landscape Portrait Landscape	Comments and Markups Summarize Comments 3.5 × 11 Inches
Page Setup	Print Cancel